

ROC PS/2 Server Interface Unit for Smart KVMs

MODEL NUMBER: 0SU51078



Description

The ROC PS/2 Server Interface Module connects to the HD15 port and PS/2 ports on a computer/server, and converts them to a single RJ45 connector. Ordinary Cat5e patch cables can then be used to connect the computer/server to the switch ports on a Smart KVM switch. Use of Cat5e cables frees up space in the installation that would be filled by traditional, thicker KVM cables.

Features

- Needed to connect a PS/2 Server to a Smart KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply needed
- Allows a recommended maximum distance of 100ft from KVM to Server via Cat5e cable
- Compact and lightweight design

Specifications

OVERVIEW	
UPC Code	654518209358
Accessory Type	Server Interface Unit
Accessory Class	KVM Switch Accessories
CONNECTIONS	
Side B - Connector 2	(2) MINI DIN-6 (MALE)
PHYSICAL	
Shipping Weight (lbs.)	0.40

Highlights

- Needed to connect a PS/2 Server to a Smart KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply needed
- Allows a recommended maximum distance of 100ft from KVM to Server via Cat5e cable
- Compact and lightweight design

System Requirements

- Smart KVM Switch
- Computer with a VGA video port
- Computer with PS/2 keyboard and mouse ports

Package Includes

- ROC PS/2



Powering Business Worldwide



Shipping Weight (kg)	0.18
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.