



Powering Business Worldwide

## Eaton 5P G2 3000VA 3000W 120V Line-Interactive UPS - 1x L5-30R and 6x 5-15/20R Outlets, Pre-Installed Cybersecure Network Card, 2U Rack/Tower

MODEL NUMBER: 5P3000RTNG2



Provides enterprise-class battery backup and pure sine wave output for servers, switches, edge computing and other critical networking equipment.

### Features

#### 3kVA/3kW/120V Battery Backup for Edge Computing

This 5P G2 line-interactive UPS system provides reliable battery backup and AC power protection for servers, switches and other mission-critical IT equipment in edge computing environments, server rooms and network closets. The 5P3000RTNG2 protects more connected devices by providing 20 percent more wattage compared to traditional UPS systems. Pure sine wave output provides stable, highquality power, while unity power factor (1.0) ensures maximum usable watts at each power rating.

#### Reliable Battery Backup with Enhanced Management

Exclusive ABM technology increases battery life by 50 percent by optimizing the charging process. It also closely monitors battery health to provide advanced notice when batteries need replacing.

#### Pre-Installed Gigabit Network Interface Offers 24/7 Remote Access

The NETWORK-M3 cybersecure network management card enables full remote configuration and management, including load shedding, reboots of connected equipment and safe shutdowns. UPS firmware can also be flashed remotely through the NETWORK-M3 without dropping the load, so you don't have to plan for downtime. The card meets both UL 2900-1 and IEC 62443-4-2 standards for cybersecurity, which were developed to address the vulnerability of connected devices to known malware/exploits and to protect businesses from these risks.

#### NEMA Outlets Protect Your Connected Components

One L5-30R and six 5-15/20R outlets provide connected equipment with pure sine wave AC output and allow you to monitor power consumption down to the outlet group level. Four 5-15/20R outlets are grouped into two load banks that let you shed non-critical loads to extend runtime for critical loads.

#### Automatic Voltage Regulation (AVR) Corrects Low- and High-Voltage Conditions

AVR protects your equipment from incremental hardware damage, data loss and performance problems caused by brownouts and overvoltages. The 5P3000RTNG2 can correct brownouts as low as 89V and overvoltages as high as 151V back to nominal 120V power continuously, all while keeping the battery fully charged and ready to take over in case of power failure.

### Highlights

- Unity power factor (1.0) delivers full rated power to support modern IT loads
- Pure sine wave output ensures compatibility and stability for sensitive equipment
- Exclusive ABM technology increases battery life by 50%
- Rack-friendly design is shorter in depth and 25% lighter than earlier 5P model
- Pre-installed NETWORK-M3 Gigabit network card enables full remote access and control

### Package Includes

- 3000VA 3000W 120V 5P G2 Line-Interactive UPS
- NETWORK-M3 Gigabit network management card
- USB cable
- RS-232 cable
- Rack-mounting hardware
- Tower support stands
- User documentation



Powering Business Worldwide

#### LCD Interface Keeps You Informed at a Glance

The five-button graphical LCD provides useful information about the UPS itself, load status, events, measurements and settings. To save energy, the LCD switches to the screen saver after five minutes of inactivity. The multi-color LED status bar stays illuminated so you can always check power status at a glance.

#### Advanced Communications Ports Allow for Automatic Saves and Shutdowns

RS-232 and USB ports connect to a serial-enabled or USB-enabled device for a variety of communication options (cables are included). The RPO/ROO connector permits emergency shutdown or remote restart of all connected equipment.

#### Easy Installation Options

You can mount the 5P3000RTNG2 in just 2U of space in an EIA-standard 19-inch rack using the included 4-post rail kit. You can also install the UPS in a tower format with the included support stands. The 10-foot (3-meter) power cord with NEMA L5-30P plug connects to a compatible AC outlet.

## Specifications

OVERVIEW	
UPC Code	786687110958
UPS Type	Line-Interactive
INPUT	
Input Phase	Single-Phase
Rated input current (Maximum Load)	24
Nominal Input Voltage(s) Supported	120V AC
Nominal Input Voltage Description	Normal Mode: 120Vac (89-151 Vac) Extended Mode: 120V (70-153 Vac at <87% load)
UPS Input Connection Type	L5-30P
UPS Input Cord Length (ft.)	10
UPS Input Cord Length (m)	3.1
Recommended Electrical Service	30A 120V
Maximum Input Amps	24
Input Plug Type	NEMA L5-30P
OUTPUT	
Output Capacity (VA)	3000
Output Capacity (kVA)	3
Output Capacity (Watts)	3000
Output Capacity (kW)	3
Power Factor	1
Nominal Voltage Details	100V, 120V, 125V
Frequency Compatibility	50 / 60 Hz



Powering Business Worldwide

Load Management Receptacles	2 Banks (2 outlets per bank)
Output AC Waveform (AC Mode)	Sine wave
Output (Watts)	3000
Output AC Waveform (Battery Mode)	Pure Sine wave
Nominal Output Voltage(s) Supported	120V
Output Receptacles	(6) 5-15/20R; (1) L5-30R
Individually Controllable Load Banks	No
<b>BATTERY</b>	
Battery Type	Valve Regulated Lead Acid (VRLA)
Runtime Full Load (min.)	3 min. (3000W)
Runtime Half Load (min.)	9 min. (1500W)
Expandable Runtime	No
DC System Voltage (VDC)	72
Battery Recharge Rate (Included Batteries)	9 Hours
Battery Access	Battery Door
Lithium Batteries	No
Battery Management	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
<b>VOLTAGE REGULATION</b>	
Voltage Regulation Description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 89 to 151Vac (Normal) 70 to 153Vac (Extended)
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Front Panel LCD Display	LCD graphical display
Switches	5 Buttons: Esc, Up, Down, Enter, On/Off; RPO / ROO; Relay Out
Audible Alarm	Audible alarm indicates utility failure, low-battery, overload, other UPS/Battery fault or remote shutdown
LED Indicators	3 status-indicating LEDs (normal, battery mode, alarm); LED light Bar (Blue = Nominal, Yellow = Warning, Red = Alarm)
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC Suppression Joule Rating	380
UPS AC Suppression Response Time	Instantaneous
AC Suppression Joule Rating	380
<b>PHYSICAL</b>	
Primary Form Factor	Rackmount



Powering Business Worldwide

Rack Height	2U
Cooling Method	Fan
Included Mounting Accessories	Rackmount hardware, Tower support stands
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount; Tower
Maximum Device Depth (cm)	60.30
Maximum Device Depth (in.)	23.740
Maximum Device Depth (mm)	603
Minimum Required Rack Depth (cm)	68.58
Minimum Required Rack Depth (inches)	27
Minimum Required Rack Depth with External Battery Pack (cm)	69
Minimum Required Rack Depth with External Battery Pack (in.)	27
Minimum Required Rack Depth without External Battery Pack (cm)	69
Minimum Required Rack Depth without External Battery Pack (in.)	27
Primary UPS Depth (mm)	603
Primary UPS Height (mm)	93
Primary UPS Width (mm)	438
UPS Housing Material	Steel
UPS Power Module Weight (kg)	33.80
UPS Power Module Weight (lbs.)	74.520
Unit Dimensions (hwd / in.)	3.670 x 17.240 x 23.740
Unit Weight (lbs.)	74.520
Unit Weight (kg)	33.80
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	5° to 122°F (-15° to 50°C)
Relative Humidity	20-90% non-condensing
AC Mode Efficiency Rating (100% Load)	97.5
Operating Elevation	9842ft (3000m)
Storage Elevation (ft.)	9842
Audible Noise	40dB
<b>COMMUNICATIONS</b>	



Powering Business Worldwide

Network Management Cards	&nbsp;<a class="productLink" href="//tripplite.eaton.com/sku~Network-M3">Network-M3</a>&nbsp;</td>
Network Management Card Description	Bundled Network-M3 network card
Communications Interface	Included network card; RS-232; USB (HID enabled)
<b>LINE / BATTERY TRANSFER</b>	
Transfer Time	10ms Typical
Low Voltage Transfer to Battery Power (Setpoint)	89V +/-3%
High Voltage Transfer to Battery Power (Setpoint)	151V +/-3%
<b>FEATURES &amp; SPECIFICATIONS</b>	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
High Availability UPS Features	Automatic Voltage Regulation (AVR); Sine wave output
<b>APPLICATIONS</b>	
UPS Applications	High-End Desktop/Small Network; Large Network; Audio/Video
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CAN/CSA-C22.2 No. 107.3 (Canada); ICES (Canada); IEC/EN 62040; UL 1778
Product Compliance	ENERGY STAR Qualified; FCC Part 15 Class A (USA); RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (U.S. & Canada)	3-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.