



Powering Business Worldwide

Eaton Internal Replacement Battery Cartridge (RBC) for Select 2kVA to 2.2kVA UPS Systems and EBM

MODEL NUMBER: 744-A3121



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton Online UPS system or Extended Battery Modules (EBMs).

Features

UPS Replacement Battery Cartridge for Select Eaton 9PX UPS Systems

This UPS backup battery replacement is compatible with Tripp Lite series SmartOnline SU2200RTLCD2U (2023 redesign), SU2200RTLCDN (2023 redesign), and SUI2200LCD2U (2023 redesign) and 9PX2000RT, 9PX2000RTN and 9PX2200GRT UPS systems, as well as BP72RT and 9PXE72RT extended battery modules (EBMs). Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A3121 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A3121 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your UPS system.

Specifications

OVERVIEW	
UPC Code	743172089779
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)

Highlights

- Replacement battery backup for select Eaton 2kVA–2.2kVA 9PX and SmartOnline UPS or EBM
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

System Requirements

Compatible only with Tripp Lite series SmartOnline SU2200RTLCD2U (2023 redesign), SU2200RTLCDN (2023 redesign), and SUI2200LCD2U (2023 redesign), and the 9PX2000RT, 9PX2000RTN and 9PX2200GRT UPS systems, as well as BP72RT and 9PXE72RT EBM.

Package Includes

744-A3121 Internal Replacement Battery Cartridge



Powering Business Worldwide

Battery Replacement Description	Hot-swappable, user replaceable batteries. Re-use existing wiring harness.
Hot Swap Battery	Yes
PHYSICAL	
Unit Dimensions (hwd / in.)	2.640 x 8.270 x 18.310
Unit Weight (lbs.)	34.8
Unit Weight (kg)	15.79
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
APPLICATIONS	
Used With	9PXEBM72RT, 9PX2000RT, 9PX2200GRT, 9PX2000RTN, SU2200RTXLCD2U (2023 redesign), SU2200RTXLCDN (2023 redesign), SUINT2200LCD2U (2023 redesign), BP72RT
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.