

Eaton Internal Replacement Battery Cartridge (RBC) for Select 9SX 2-3kVA UPS Systems

MODEL NUMBER: 744-A4313



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 9SX UPS system.

Features

UPS Replacement Battery Cartridge for Select Eaton 9SX UPS Systems

This UPS backup battery replacement is compatible with Eaton's 9SX2000, 9SX2000G, 9SX3000, 9SX3000G, 9SX3000GL and 9SX3000HW UPS systems. Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A4313 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A4313 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 9SX UPS system.

Specifications

OVERVIEW	
UPC Code	786689575571
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Battery Replacement Description	Re-use existing wiring harness

Highlights

- Replacement battery backup for select Eaton 2kVA–3kVA 9SX UPS systems
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

System Requirements

Compatible only with Eaton's 9SX2000, 9SX2000G, 9SX3000, 9SX3000G, 9SX3000GL and 9SX3000HW UPS systems

Package Includes

744-A4313 Internal Replacement Battery Cartridge



Powering Business Worldwide

1000 Eaton Boulevard
Cleveland, OH 44122
United States

Hot Swap Battery	Yes
PHYSICAL	
Unit Dimensions (hwd / in.)	11.400 x 16.400 x 16.900
Unit Weight (lbs.)	47.6
Unit Weight (kg)	21.59
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
APPLICATIONS	
Used With	9SX2000, 9SX2000G, 9SX3000, 9SX3000G, 9SX3000GL 9SX3000HW
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.