




Powering Business Worldwide

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

# Eaton Internal Replacement Battery Cartridge (RBC) for 5P2200 and 5P2200RT 5P UPS Systems

MODEL NUMBER: 744-A4852



### Highlights

- Replacement battery backup for Eaton 5P2200 and 5P2200RT 5P UPS systems
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships pre-wired and ready for immediate installation to prevent downtime

### System Requirements

Compatible only with Eaton's 5P2200 and 5P2200RT UPS systems

### Package Includes

744-A4852 Internal Replacement Battery Cartridge

UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 5P UPS system.

### Features

#### UPS Replacement Battery Cartridge for Select Eaton 5P UPS Systems

This UPS backup battery replacement is compatible with Eaton's 5P2200 and 5P2200RT UPS systems. Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

#### Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A4852 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A4852 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 5P UPS system.

## Specifications

OVERVIEW	
UPC Code	037332282323
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Battery Replacement Description	Re-use existing wiring harness



Powering Business Worldwide

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

Hot Swap Battery	Yes
<b>PHYSICAL</b>	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
<b>APPLICATIONS</b>	
Used With	5P2200, 5P2200RT
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.