



1U Rack-Mount Console with 19 in. LCD, 1920 x 1080 (1080p), DVI or VGA Video, TAA

MODEL NUMBER: **B021-000-19-HD2**

Description

The [B021-000-19-HD2](#) 1U Rack-Mount Console combines a full keyboard, numeric keypad, touchpad and 19-inch color LCD for easy all-in-one control of a computer, server or KVM switch. Easy to install and simple to operate, it slides neatly into 1U of rack space when not in use.

The rear DVI-I console port supports both digital and analog video signals for connecting to a DVI- or VGA-enabled server or KVM switch (a DVI to VGA adapter is included). The LCD screen supports video resolutions up to 1920 x 1080 (1080p). Video settings of the connected computer are automatically adjusted for optimal display on the LCD screen. USB 2.0 pass-through ports on the front and rear allow you to connect a USB peripheral, such as a flash drive or CAC card reader, to your computer with a USB cable (sold separately).

The [B021-000-19-HD2](#) mounts into 1U of space in an EIA-standard 19-inch rack using the included mounting brackets and user-supplied screws. Simply pull out the steel drawer and flip up the screen when needed, then slide it back into the rack in automatic sleep mode when you're finished. This keeps the keyboard and screen from blocking access to rack equipment when the console is not in use.

This console is compatible with all major operating systems and KVM switches with a VGA or DVI monitor port and USB keyboard/mouse ports. This enables the [B021-000-19-HD2](#) to be integrated into an existing system to provide secure management of critical network systems without a major investment in new hardware.

Features

Space-Saving Console for IT Environments Where Rack Space Is Limited

- 19 in. LCD monitor, keyboard, numeric keypad and touchpad
- All-in-one control of computer, server or KVM switch
- Supports video resolutions up to 1920 x 1080 (1080p)
- Detachable 6 ft. AC power cord with NEMA 5-15P and C13 connectors

Accepts Digital and Analog Video Signals

- DVI-I port allows connection to DVI digital or VGA analog server or KVM switch
- DVI to VGA adapter included
- DDC2B emulation automatically adjusts video settings for optimal display on monitor

USB 2.0 Pass-Through Ports

- Front and rear ports allow easy connection of USB peripheral, such as flash drive or CAC card reader
- USB cable sold separately

Highlights

- DVI-I port supports both digital and analog video signals
- 19 in. LCD screen supports video resolutions up to 1920 x 1080
- USB pass-through port for connecting USB peripherals
- Goes into automatic sleep mode when cover is closed
- Compatible with all major operating systems

System Requirements

- Computer, server or KVM switch with DVI or VGA monitor and USB keyboard/mouse ports
- C13 to 5-15P power cord included. P054-006 (C13 to SCHUKO) and P056-006-10A (C13 to BS1363) power cords available to purchase separately for use internationally.

Package Includes

- 1U rack-mount console
- KVM cable kit (DVI-I, USB)
- DVI to VGA adapter
- Detachable AC power cord with NEMA 5-15P and C14 connectors, 6 ft.
- Mounting brackets
- Owner's manual



Convenient Space-Saving Design

- Mounts in 1U of space in EIA-standard 19 in. 2- and 4-post racks
- Slides neatly out of sight when not in use
- Goes into automatic sleep mode when cover is closed
- Rack-mounting brackets included

Supports Multiple Platforms for Maximum Flexibility

- Compatible with all major operating systems, including Windows®, Mac OS®, Linux®, UNIX® and Solaris™
- Compatible with KVM switches with VGA or DVI port and USB keyboard/mouse ports

TAA-Compliant

- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

MODEL TEXT	
Key Benefit	Space-saving console features 19 in. 1080p LCD monitor, keyboard, numeric keypad and touchpad for easy all-in-one control of a computer, server or KVM switch. Ideal for IT environments where rack space is limited.
OVERVIEW	
Users	1
INPUT	
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 115V AC; 120V AC; 127V AC; 140V AC; 200V AC; 208V AC; 220V AC; 230V AC; 240V AC
Electrical Consumption	(Line Mode) 30W / (Standby Mode) 5W
Input Frequency	50/60Hz
Input Current	120V (1.2A) / 230V (0.7A)
PHYSICAL	
Unit Dimensions (hwd / in.)	1.7 x 18.78 x 27.26
Unit Dimensions (hwd / cm)	4.32 x 47.7 x 69.24
Unit Weight (lbs.)	27.78
Unit Weight (kg)	12.60
Color	Black
ENVIRONMENTAL	



Operating Temperature Range	32 to 104 F (0 to 40 C)
Storage Temperature Range	-13 to 140 F (-25 to 60 C)
Relative Humidity	20% to 90% (Non-Condensing)
BTUs	(Line Mode) 102 BTU/Hr / (Standby Mode) 17.06 BTU/Hr
COMMUNICATIONS	
IP Remote Access	0
CONNECTIONS	
Ports	0
PC/Server Connections	DVI; USB; VGA
SPECIAL FEATURES	
Cat5 KVM Switch	0
CERTIFICATIONS	
Certifications	UL 60950-1 (USA), CAN/CSA (Canada), FCC Part 15 Class A, CE, IEC 60950-1
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>