

2-Port Compact PS/2 KVM Switch with Audio and Cable

MODEL NUMBER: **B004-VPA2-K-R**



Description

The B004-VPA2-K-R is a 2-port Compact PS/2 KVM Switch with optional audio and microphone switching function. It allows you to access, control, boot and reboot two PS/2-enabled computers from a single console (keyboard, monitor and mouse). The independent audio/mic switching function allows an uninterrupted audio experience - you can continue listening to audio even when you switch to the other computer. Compatible with all major operating systems.

Features

- Fast, easy switching via keyboard hot keys or push buttons
- Plug-and-play setup - no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice
- Compact design saves desk space
- Does not require an AC adapter
- Compatible with all major operating systems
- Includes two, 6ft Cable Kits

Highlights

- Fast, easy switching via keyboard hot keys or push buttons
- Allows sharing of audio components between systems; listen to music from one computer while accessing another
- Compact design saves desk space
- No software or AC adapter required
- (x2) 6ft PS/2 KVM Cable kits and (x2) 6ft 3.5mm Audio Cable Kits included
- Compatible with all major operating systems

System Requirements

- Console: VGA, SVGA or Multisync Monitor, PS/2 Keyboard and PS/2 Mouse
- Computers: VGA, SVGA or Multisync Monitor Port, PS/2 Keyboard Port and PS/2 Mouse Port
- Audio (Optional): Speakers with standard 3.5mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

Package Includes

- Compact 2-port PS/2 KVM Switch with Audio
- (2) 6ft PS/2 KVM Cable Kits and (2) 6ft 3.5mm Audio Cable Kits



- Owner's Manual with Warranty Information

Specifications

| OVERVIEW | |
|---|------------------------------|
| UPC Code | 037332140050 |
| Console | No |
| Max CPU | 2 |
| Technology | PS/2; VGA/SVGA; Stereo Audio |
| PHYSICAL | |
| Color | Black |
| LCD Monitor (cm) | Not Applicable |
| LCD Monitor (in.) | Not Applicable |
| Shipping Dimensions (hwd / cm) | 7.62 x 18.80 x 19.30 |
| Shipping Dimensions (hwd / in.) | 3.00 x 7.40 x 7.60 |
| Shipping Weight (kg) | 0.86 |
| Shipping Weight (lbs.) | 1.90 |
| ENVIRONMENTAL | |
| BTUs | 17.065 |
| COMMUNICATIONS | |
| Port Control | Push Buttons, Hotkeys |
| IP Remote Access | No |
| CONNECTIONS | |
| Ports | 2 |
| PC/Server Connections | PS/2; VGA |
| Included KVM Cable (Equipment Side) - Connector 1 | HD15 (Male) |
| Included KVM Cable (Equipment Side) - Connector 2 | (x2) MiniDIN6 (Male) |
| Included KVM Cable (Equipment Side) - Connector 3 | (x2) 3.5mm (Male) |
| Local Console Ports - Port 3 | (x2) 3.5mm (Female) |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| FEATURES & SPECIFICATIONS | |
|--------------------------------------|-------------------------|
| Number of Users | 1 |
| NIAP-Certified Secure | No |
| Cat5 KVM Switch | No |
| STANDARDS & COMPLIANCE | |
| Certifications | FCC, CE, RoHS Compliant |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>