

UPS Battery Pack for SV Series, 3-Phase UPS, No Battery - External

MODEL NUMBER: **BP240V370NB**



Houses user-supplied batteries to extend runtime of a Tripp Lite SV-Series UPS.

Features

Add Batteries to Empty Cabinet to Extend the Runtime of SV-Series UPS Systems Tripp Lite's BP240V370NB consists of an empty battery cabinet that requires 40 user-supplied 12V 100Ah sealed lead acid batteries (CSB model GPL 121000 or equal). When populated with user-supplied batteries, this external backup battery pack extends runtime for SV-Series UPS systems. Up to three external battery pack cabinets may be connected in parallel to increase runtime.

Enjoy Compatibility with SV-Series UPS Systems The BP240V370NB external UPS battery pack uses a +/- 120V DC configuration and must be hardwired to a compatible UPS. Circuit breakers provide overcurrent protection. The BP240V370NB is compatible with Tripp Lite UPS models that begin with SV20, SV40, SV60, SV80, SV100, SV120 and SV140.

Maintain a Uniform Look in Network Environments Made of powder-coated steel, the battery cabinet is designed to match the SV-Series UPS systems to keep a consistent look in your server room or data center. The cabinet door is lockable to control access to batteries. The top of the cabinet has conduit knockouts for user-supplied power output cables. Front and rear vents allow the free flow of warm air out of the cabinet.

One-Year Warranty The BP240V370NB is backed by a one-year limited warranty, ensuring reliability and performance.

Specifications

OVERVIEW	
UPC Code	037332231031
INPUT	
Input Phase	3-Phase

Highlights

- Extends runtime of SV-Series UPS systems; +/- 120V DC configuration
- Requires 40 user-supplied 12V 100Ah sealed lead acid batteries
- Requires hardwiring; breakers offer overcurrent protection
- Up to 3 packs may be connected in parallel to increase runtime

Applications

- House an external battery backup pack for an SV-Series 3-phase UPS system
- Provide extended battery runtime for an SV-Series 3-phase UPS system
- Connect up to 3 battery pack cabinets in parallel to further extend runtime for mission-critical equipment

System Requirements

- Compatible SV-Series UPS System
- 40 user-supplied 12V 100Ah sealed lead acid batteries (CSB model GPL 121000 or equal)

Package Includes

- BP240V370NB External Battery Pack (No Batteries)
- Owner's manual

BATTERY	
Expandable Runtime	Yes
DC System Voltage (VDC)	+/- 120VDC
UPS Connection	Hardwire (contractor supplies wiring - see Owner's Manual for requirements and installation information)
PHYSICAL	
Material of Construction	Steel
Rack Height	0U
External Battery Pack Form Factor	Tower
Installation Form Factors Supported with Included Accessories	Tower
Shipping Dimensions (hwd / in.)	80.31 x 28.74 x 48.00
Shipping Weight (kg)	322.05
Unit Dimensions (hwd / in.)	78.940 x 25.470 x 43.300
Unit Dimensions (hwd / cm)	200.5 x 64.7 x 110.0
Unit Weight (lbs.)	266
Unit Weight (kg)	120.66
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty