

## External Battery Pack for select Tripp Lite 3-Phase UPS Systems (BP480V300)

MODEL NUMBER: **BP480V300**



### Highlights

- Extends runtime of modular series Tripp Lite UPS Systems using special +/- 240VDC configuration
- Hardwire installation
- Internal DC disconnect
- 10 year design lifespan
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Package Includes

- BP480V300 External Battery Pack
- Warranty information
- Owner's Manual

### Description

Tripp Lite's BP480V300 External Battery Pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes internal disconnect for battery isolation. Compatible UPS Systems: SVX30K to SVX210K, S3M30KX/KXD to S3M200KX/KXD, SU40K, SU60K, SU80K, SU20KX, SU40KX, SU60KX, SU80KX, SU60KTV and SU80KTV only.

### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS Systems
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- 10 year design lifespan

## Specifications

OVERVIEW	
UPC Code	037332184955
INPUT	
Input Phase	3-Phase
BATTERY	
Expandable Battery Runtime	Multiple battery packs can be daisy-chained to the UPS for extended runtime
Expandable Runtime	Yes
DC System Voltage (VDC)	+/- 240VDC
UPS Connection	Hardwire (contractor supplies wiring - see Owner's Manual for gauge recommendations)

Typical Battery Lifespan	10 year design lifespan
<b>PHYSICAL</b>	
Material of Construction	Steel
Rack Height	48U
External Battery Pack Form Factor	Tower
Installation Form Factors Supported with Included Accessories	Tower
Minimum Required Rack Depth (cm)	83.82
Minimum Required Rack Depth (inches)	33
Shipping Dimensions (hwd / in.)	85.00 x 44.00 x 40.00
Shipping Dimensions (hwd / cm)	215.90 x 111.76 x 101.60
Shipping Weight (lbs.)	2980.00
Shipping Weight (kg)	1,351.71
Unit Dimensions (hwd / in.)	78.700 x 36.000 x 29.500
Unit Dimensions (hwd / cm)	199.9 x 91.4 x 74.9
Unit Weight (lbs.)	2866
Unit Weight (kg)	1,300.00
Unit Weight Details	Floor loading 350 ilbs per sq. ft. / 1714 kg per sq. meter
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	UKCA; Trade Agreements Act (TAA)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	1-year limited warranty