

# External UPS Battery Pack, 40 65Ah Batteries Included - Compatible S3MX-Series 3-Phase UPS System

MODEL NUMBER: **BP480V65**



Backup battery pack provides extended runtime for compatible Tripp Lite S3MX-Series 3-phase UPS systems.

## Description

Tripp Lite's BP480V65 External Battery Cabinet offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes internal disconnect for battery isolation. Compatible UPS Systems: S3M30KX-NIB, S3M40KX-NIB, S3M60KX, S3M80KX, S3M100KX, S3M120KX, S3M160KX and S3M200KX

## Features

**+/-240VDC Backup Battery Pack Gives Your Compatible UPS System Extended Runtime**The BP480V65 is compatible only with Tripp Lite's 3-phase S3M30KX-NIB, S3M40KX-NIB, S3M60KX, S3M80KX, S3M100KX, S3M120KX, S3M160KX, S3M200KX and other UPS systems that specify the use of this battery pack. The UPS battery pack consists of a steel battery cabinet and 40 sealed 65Ah lead acid batteries. Hardwire installation is safe and simple. Circuit breakers provide overcurrent protection. Internal disconnect for battery isolation is included.

**Daisy-Chain Multiple Cabinets for Even Longer Extended-Run Operation**Multiple battery pack cabinets may be connected in parallel to provide the 3-phase UPS system with more runtime. Up to three external battery packs may be connected to the S3M30KX-NIB, S3M40KX-NIB, S3M60KX and S3M80KX. The S3M100KX, S3M120KX, S3M160KX and S3M200KX units can handle as many as seven BP480V65s connected in parallel.

**One-Year Warranty**The BP480V65 is backed by a one-year warranty, ensuring reliability and performance.

## Specifications

### Highlights

- Extends runtime of compatible UPS systems using special +/- 240VDC configuration
- Black steel cabinet matches UPS systems to give your server room a consistent look
- Requires hardwire installation; circuit breakers provide overcurrent protection
- Multiple battery pack cabinets may be connected in parallel to increase runtime

### Applications

- Extend the runtime of your compatible Tripp Lite UPS system to maintain operation during all power conditions
- Daisy-chain to multiple additional battery packs to provide even longer extended-run operation for backing up essential equipment in your data center or server room

### System Requirements

- Tripp Lite S3M30KX-NIB, S3M40KX-NIB, S3M60KX, S3M80KX, S3M100KX, S3M120KX, S3M160KX, S3M200KX or other UPS system specifying compatibility with this external battery pack

### Package Includes

- BP480V65 External Battery Pack with cable jumpers for 40 x 65Ah batteries
- 40 x 65Ah Batteries palletized separately
- Cable for jack, 32 in. (81.3 cm), 1/0 AWG
- Attachment hardware for battery cable
- Owner's manual

### OVERVIEW

UPC Code

037332231093



Powering Business Worldwide



| INPUT   |  |
|---|--|
| Input Phase   | 3-Phase  |
| BATTERY   |  |
| Expandable Runtime  | Yes  |
| DC System Voltage (VDC)                                       | +/- 240VDC   |
| UPS Connection  | Hardwire (contractor supplies wiring - see Owner's Manual for gauge recommendations) |
| Typical Battery Lifespan                                      | 10 year design lifespan  |
| PHYSICAL  |  |
| Material of Construction                                      | Steel  |
| Rack Height   | 34U  |
| External Battery Pack Form Factor                             | Tower  |
| Installation Form Factors Supported with Included Accessories | Tower  |
| Minimum Required Rack Depth (cm)                              | 121.92   |
| Minimum Required Rack Depth (inches)                          | 48   |
| Shipping Dimensions (hwd / in.)                               | 8.00 x 7.00 x 14.00  |
| Shipping Dimensions (hwd / cm)                                | 20.32 x 17.78 x 35.56  |
| Shipping Weight (lbs.)  | 45.00  |
| Shipping Weight (kg)  | 20.41  |
| Unit Dimensions (hwd / in.)                                   | 59.050 x 32.520 x 44.680   |
| Unit Dimensions (hwd / cm)                                    | 149,9 x 82,6 x 113,5   |
| Unit Weight (lbs.)  | 2110.7   |
| Unit Weight (kg)  | 957.40   |
| WARRANTY & SUPPORT  |  |
| Product Warranty Period (Worldwide)                           | 1-year limited warranty  |

1000 Eaton Boulevard  
 Cleveland, OH 44122  
 United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
 Eaton is a registered trademark. All other trademarks  
 are the property of their respective owners.