


EnviroSense2 (E2) Water Leak Detection Sensor

MODEL NUMBER: E2SLD



Leak detection sensor works with compatible UPS or PDU to detect leakage of water or other electrically conductive fluid.

Features

Receive an Immediate Alert in Case of Water Leak in Your Data Center or Wiring ClosetThe E2SLD mounts near cooling units and other IT equipment in your server room to detect water leakage or leakage of any electrically conductive fluid. It supports a Normally Open contact closure connection. When liquid comes in contact with both sensor contacts, an alert notification is sent to you via web, SNMP, telnet or SSH management interfaces.

Easy to Mount on a Raised FloorThe sensor is constructed from fire-retardant ABS plastic. Mount the sensor to a wood, metal or concrete surface about three millimeters above the raised floor surface. Use the included mounting screws, double-sided tape or a user-supplied adhesive. A screw terminal cover is included to protect the wire terminals from damage or interference.

Required Accessories: WEBCARDLX or LX Platform and E2MTHDIThe E2SLD must be used with a compatible Tripp Lite UPS system or PDU equipped with the WEBCARDLX or LX Platform interface, along with an E2MTHDI EnviroSense2 (E2) Environmental Sensor Module with polarity markings (sold separately). The E2MTHDI supports E2SLD and one additional contact closure sensor.

TAA-Compliant for GSA Schedule PurchasesThe E2SLD is compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

5-Year Warranty and Environmentally Responsible DesignThe E2SLD comes with a 5-year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

Highlights

- Mounts 3 mm above raised floor to detect water or other fluid leakage
- Must be used in conjunction with WEBCARDLX or built-in LX Platform interface along with E2MTHDI
- Includes mounting materials for quick and easy installation
- Made from durable fire-retardant ABS to ensure long life in your data center
- Ideal tool for protecting your IT, data center or building maintenance application

System Requirements

- Compatible Tripp Lite UPS or PDU equipped with WEBCARDLX or LX Platform interface and E2MTHDI with polarity markings

Package Includes

- E2SLD EnviroSense2 (E2) Water Leak Detection Sensor
- Screw terminal cover
- 22 AWG connection wire, 15 ft.
- Double-sided adhesive tape
- (2) #6 multi-surface mounting screws
- Owner's manual

Specifications

OVERVIEW



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

UPC Code	037332213617
Power Management Type	Sensors
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.26 x 4.49 x 6.06
Shipping Dimensions (hwd / cm)	3.20 x 11.40 x 15.39
Shipping Weight (lbs.)	0.22
Shipping Weight (kg)	0.10
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>