

Eaton 9PX Maintenance Bypass for Select 8kVA to 11kVA 9PX UPS Systems, Hardwired Input/Output, 3 L6-30R Outlets, 3U Rack/Tower

MODEL NUMBER: MBP11K208



Reroutes utility power to keep essential equipment operational while you're servicing or replacing a UPS system.

Features

Compatible with Select Eaton 8kVA to 11kVA 9PX UPS Systems

The MBP11K208 works with Eaton's 9PX8K, 9PX8KHW, 9PX8KTF5, 9PX11K, 9PX11KHW, 9PX11KTF11 and 9PX11KTF5 UPS systems. The bypass switch lets you service or replace the UPS system without powering down any equipment and risking costly downtime. Power passes directly from the PDU to equipment.

Versatile Connection and Installation Options

The MBP11K208 features hardwired input and output connections. Three NEMA L6-30R outlets also allow load connection. You can mount the maintenance bypass switch in 3U of space in an EIA-standard 19-inch rack using the included 4-post rail kit. You can also adapt it for tower or wall installation using the included hardware.

Specifications

| OVERVIEW | |
|---------------------------|---------------------------|
| UPC Code | 743172043610 |
| Accessory Type | Bypass Panel (Rack-Mount) |
| Accessory Class | UPS Accessories |
| INPUT | |
| UPS Input Connection Type | Hardwire |
| OUTPUT | |

Highlights

- Isolates UPS from connected loads for maintenance without powering down equipment
- Designed for 3U rack, tower or wall mounting using the included installation hardware
- Compatible with Eaton's 8kVA to 11kVA 9PX UPS systems

System Requirements

Compatible with Eaton's 9PX8K, 9PX8KHW, 9PX8KTF5, 9PX11K, 9PX11KHW, 9PX11KTF11 and 9PX11KTF5 UPS systems

Package Includes

- MBP11K208 Maintenance Bypass
- (2) Input/output covers
- Input/output cover fixation kit
- (2) Conduits for UPS input/output connection
- (4) Conduit fittings
- Mounting hardware
- Installation and user manual



Powering Business Worldwide

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|---|---------------------------|
| Individually Controllable Load Banks | No |
| BATTERY | |
| Expandable Runtime | No |
| PHYSICAL | |
| Unit Dimensions (hwd / in.) | 5.100 x 13.200 x 8.700 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Relative Humidity | 0-95% non-condensing |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (U.S. & Canada) | 3-year limited warranty |



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.