

## Thunderbolt 3 to Dual DisplayPort Adapter - 4K/5K @ 60 Hz, M/2xF, 4:4:4, Silver

MODEL NUMBER: MTB3-002-DP



Connects your MacBook, notebook or PC's Thunderbolt 3 port to two 4K DisplayPort monitors or one 5K DisplayPort monitor.

### Features

**Thunderbolt 3 Adapter Transmits 4K x 2K Video to 2 DisplayPort Monitors at the Same Time** This Thunderbolt 3 to Dual DisplayPort Adapter (M/2xF) connects the Thunderbolt 3 port on your computer, tablet, laptop, notebook or MacBook to two 4K DisplayPort monitors simultaneously. Or, if you need even more resolution, it also transmits a 5K (!) audio/video signal to a single DisplayPort monitor.

**An Ideal Tool for Video Editing or Multitasking at Home or the Office** With this Thunderbolt 3 adapter's high bandwidth of 40 Gbps, you can more efficiently run applications that demand heavy resources. For instance, editing 4K video is easier with one monitor used for raw video playback and the other displaying your fresh cut. Home/office multitasking is more efficient with two monitors placed side by side on your workstation. And your video presentation or digital signage looks vivid and enticing in stunning 4K.

**Enjoy the Clarity of True 4K Video with Audio and 4:4:4 Color** This 4K DisplayPort adapter supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz for crystal-clear picture and sound on two DisplayPort monitors. Or you can connect to one 5K monitor at video resolutions up to 5120 x 2880 (5K x 2K) at 60 Hz for an even sharper image. The MTB3-002-DP is compatible with HDCP 2.2 and DisplayPort 1.4 standards for carrying HDR (high dynamic range) signals. It also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor, as well as 48-bit Deep Color (16 bits per channel). Because the adapter supports both video and audio, no additional cabling is needed for sound.

**Reversible Thunderbolt 3 Connector Attaches in Either Direction** Unlike traditional USB cables that connect in only one direction, the reversible male connector plugs into a Thunderbolt 3 port in either direction for a fumble-free connection every time. Thunderbolt 3 is eight times faster than USB 3.0 with four times the video bandwidth of HDMI.

**Ready to Use Right from the Package, So You Can Plug and Play Immediately** The plug-and-play adapter requires no software or external power. Just connect the built-in cable to the Thunderbolt 3 port on your source device, and use DisplayPort cables to connect the adapter to your display(s). Because the adapter is backward compatible with non-4K displays, you can use it with 1080p monitors or other available displays, making it a convenient tool to carry in your laptop bag or backpack for use anywhere.

### Highlights

- Supports dual DisplayPort monitors at 4K resolutions of 3840 x 2160 @ 60 Hz
- Supports a single DisplayPort monitor at 5K resolutions of 5120 x 2880 @ 60 Hz
- Reversible Thunderbolt 3 plug connects in either direction for instant no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation
- Works with Mac and Windows computers and laptops with Thunderbolt 3 output

### Applications

- Watch 4K video content from a notebook or media server on two Ultra HD televisions or projectors
- Connect a MacBook to a conference table's A/V box to give a video presentation on one 5K or two 4K screens
- Attach two 4K monitors to your PC to allow easier multitasking or more convenient video editing
- Play online or PC video games that display optimal graphics
- Send Ultra HD content to digital signs or point-of-sale displays
- Connect security cameras and other A/V surveillance equipment to a central 5K display

### System Requirements



- Source device with Thunderbolt 3 port
- Display device(s) with DisplayPort input (DisplayPort 1.2 required to achieve 4K @ 60 Hz)
- Supports Windows 8, 8.1 and 10; MacOS up to 10.12

**Package Includes**

- MTB3-002-DP Thunderbolt 3 to Dual DisplayPort Adapter - 4K/5K @ 60 Hz, M/2xF, Silver
- Quick Start Guide

## Specifications

OVERVIEW	
UPC Code	037332222008
INPUT	
Bus Powered	Yes
PHYSICAL	
Color	Silver
ENVIRONMENTAL	
Operating Temperature Range	32 ~ 113F (0 ~ 45C)
Storage Temperature Range	14 ~ 158F (~10C ~ 70C)
Operating Humidity Range	10% ~ 90% RH (No Condensation)
Storage Humidity Range	10% ~ 90% RH (No Condensation)
CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	DISPLAYPORT (FEMALE)
Side B - Connector 2	DISPLAYPORT (FEMALE)
FEATURES & SPECIFICATIONS	



Max Supported Video Resolution	3840 x 2160 (4K x 2K) @ 60 Hz (Dual Displays); 5120 x 2880 (5K x 2K) @ 60 Hz (Single Display)
Displayport Specification	1.2; 1.4
HDCP Specification	2.2
USB Specification	USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
Max Supported Color Depth	48-bit Deep Color
Technology	DisplayPort
Chroma Sub Sampling	4:2:2; 4:4:4
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>