



Cat6a Keystone Jacks, 10 Pack - 4PPoE Compliant, 110/Krone, 568A/B, RJ45 Ethernet, Blue, TAA

MODEL NUMBER: N238-010-BL-6A











Allows easy 110 or Krone termination of Cat6a network cable at a patch panel, wall plate or outlet box.

Features

Simplify Cat6a Cable Termination in Your High-Speed Network Installation

These Cat6a keystone jacks snap into any standard patch panel, wall plate or outlet box to terminate a Cat6a cable. Not only will adding keystone jacks to your high-speed network give your installation a clean professional look, they also strengthen it by ensuring all future connections are effortless. Just plug a Cat6a cable into the keystone's RJ45 Ethernet port, and use a 110 or Krone punch-down tool to terminate the cable.

Support Type 4 Power over Ethernet Plus (PoE++) to Give You More Installation Choices

Because these Cat6a keystone jacks support Type 4 PoE++ (4PPoE), they can help supply the power to operate compatible PoE devices, such as security cameras, VoIP telephones, point-of-sale kiosks and access control devices. This saves you the expense and effort of purchasing, connecting and installing individual power supplies for each device. It also helps you install PoE devices in areas far away from AC outlets, such as poles or ceilings.

Meet or Exceed Current Standards for Performance

Recommended for all Cat6a cabling environments, N238-010-BL-6A keystone jacks are UL-certified and fully compliant with EIA/TIA Cat6a specifications. The keystone jacks feature a uniquely patterned printed circuit board designed for 650 MHz performance. Dual color-coded labeling is present for both 568A and 568B (258A) wiring schemes. These are ideal Cat6 keystone jacks for residential, commercial and data center in-wall ports or networking closets for installers that opt to terminate their own keystones.

TAA-Compliant for GSA Schedule Purchases

The N238-010-BL-6A is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Specifications

OVERVIEW	
UPC Code	037332284815

Highlights

- Support Type 4 PoE++ to save you expense of powering PoE devices individually
- Krone and 110 punchdown provide flexibility for both North American and European installations
- Dual-color-coded labeling for 568A/B wiring schemes allows fast, easy identification
- Work with all Cat6a cables and meet all EIA/TIA Cat6a requirements
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Compatible with all Cat6a cables
- Meet all EIA/TIA Cat6a requirements

Package Includes

- N238-010-BL-6A Cat6a Keystone Jacks, 10 Pack
- Installation instructions





Product Type	RJ45 Keystone Jack	
Technology	Cat6a	
Host Connector	110 IDC; KRONE IDC	
VIDEO		
HDR Support	No	
3D Video Supported	No	
NETWORK		
Network Ports	RJ45 (FEMALE)	
INPUT		
Input Plug Type	RJ45	
CONNECTIONS		
Number of Ports	1	
Ports	1	
PoE Capability	100W (802.3bt)	
Side A - Connector 1	110 IDC; KRONE IDC	
Side B - Connector 1	RJ45 (FEMALE)	
PoE Type	Type 4 High-Power (100W, IEEE 802.3bt)	
PHYSICAL		
Color	Blue	
Material of Construction	IDC HOUSING: PC FR; FRONT HOUSING: ABS+PC	
Connector Color	Blue	
Shipping Dimensions (hwd / in.)	9.00 x 6.97 x 0.50	
Shipping Dimensions (hwd / cm)	22.86 x 17.70 x 1.27	
Shipping Weight (lbs.)	0.19	
Shipping Weight (kg)	0.09	
Unit Dimensions (hwd / in.)	0.670 x 0.870 x 1.230	
Unit Dimensions (hwd / mm)	20.83 x 31.13 x 17	
ENVIRONMENTAL		
Operating Temperature Range	14° to 140°F (-10° to 60°C)	
Storage Temperature Range	-40° to 158°F (-40° to 70°C)	
Relative Humidity	10% to 85% RH, NON-CONDESNING	
COMMUNICATIONS		





Maximum Data Rate	10 Gbps	
Network Compatibility	1 Gbps (Gigabit); 10 Gbps	
FEATURES & SPECIFICATIONS		
DC Current Rating	1.5A	
Cable Compatibility	Cat6a	
Ethernet Support	Yes	
Recommended Category Cable	Cat6a	
Tools Necessary	Yes	
Keystone Jacks	Yes	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA C22.2 No. 182.4-M90 (Canada); UL 1863	
Product Compliance	CE (Europe); IEEE 802.3bt PoE++; RoHS; Trade Agreements Act (TAA); UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.