

Gigabit Multimode Fiber to Ethernet Media Converter, 10/100/1000 SC, International Power Supply, 1310 nm, 2,000 m (6,561 ft.)

MODEL NUMBER: N785-INT-SC



Extends your 10/100/1000 Mbps Gigabit Ethernet connection up to 2,000 m (6,561 ft.) using fast SC multimode fiber optic cabling.

Description

The economical N785-INT-SC Gigabit Multimode Fiber to Ethernet Media Converter allows you to extend your 10/100/1000 Mbps Ethernet connection up to 2,000 meters (6,561 feet) without the limitations of extra Cat5e/6 UTP cabling. Because Cat5e/6 cables are limited to only 100 meters, it is more effective to use SC multimode fiber optic cabling for greater distances.

Use copper UTP cabling to connect one 1310 nm N785-INT-SC converter to your network device, such as a computer, and another converter to a network switch. The two converters are connected by a multimode fiber optic cable with SC connectors. The N785-INT-SC supports 50/125 multimode cable up to 2,000 meters and 62.5/125 multimode cable up to 400 meters.

Monitoring and controlling your network nodes is easy with the converter's advanced features, such as automatic network speed sensing, full/half-duplex auto-detection and automatic MDI/MDI-X configuration. Six LEDs indicate the converter's Ethernet network and fiber link status at a glance.

The N785-INT-SC includes an external power supply with international plug adapters for North America (NEMA 5-15P), the United Kingdom (BS 1363), Europe (CEE 7/16 Schuko) and Australia (AS/NZS 3112). The plug-and-play fiber-to-copper media converter requires no software or drivers and is easy to set up.

Features

Extends a Gigabit Ethernet Signal up to 2,000 m (1804 ft.) Using SC Multimode Cable

- Converts UTP copper connection to duplex fiber over long distance, then back to copper at opposite end while auto-sensing the proper speed

Highlights

- RJ45 jack supports auto-MDI/MDI-X to bridge various network devices
- Supports both full- and half-duplex operation
- LEDs indicate Ethernet and fiber link status at a glance
- Includes North America, U.K., Europe and Australia plug adapters
- Plug-and-play operation with no software or drivers required

Package Includes

- N785-INT-SC Gigabit Multimode Fiber to Ethernet Media Converter, 1310 nm, 2,000 m
- External power supply (Input: 100–240V, 50/60 Hz, 0.35A; Output: 5V 2A)
- (4) International plug adapters (North America, U.K., Europe, Australia)
- Owner's manual



- Fiber optic technology more effective than Cat5e/6 over long distances
- Supports 50/125 multimode fiber optic cabling up to 2,000 m
- Supports 62.5/125 multimode fiber optic cabling up to 400 m
- Connection requires an N785-INT-SC at both ends

Advanced Monitoring and Control

- Supports automatic sensing of network speed
- Supports both full-duplex and half-duplex operation
- Supports automatic MDI/MDI-X configuration
- 6 LEDs indicate network and fiber link status at a glance

Plug-and-Play Operation

- No additional software or drivers required
- Compact unit sets up in minutes
- Durable metal housing designed to last
- Power supply includes international plug adapters for North America, U.K., Europe and Australia

Specifications

OVERVIEW	
UPC Code	037332205667
INPUT	
External Power Supply Input Specs (V / Hz / A)	100-240V, 50/60HZ, 0.35A
External Power Supply Output Specs (V / A)	5V, 2A
External Power Supply Cord Length (ft.)	4
External Power Supply Cord Length (m.)	1.2
PHYSICAL	
Color	Black
Shipping Dimensions (hwd / cm)	5.51 x 23.01 x 12.50
Shipping Dimensions (hwd / in.)	2.17 x 9.06 x 4.92
Shipping Weight (kg)	0.43
Shipping Weight (lbs.)	0.95
Unit Dimensions (hwd / cm)	2.54 x 11.94 x 6.99
Unit Dimensions (hwd / in.)	1.00 x 4.70 x 2.75



Unit Weight (kg)	0.45
Unit Weight (lbs.)	1
CONNECTIONS	
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	SC DUPLEX (FEMALE)
FEATURES & SPECIFICATIONS	
Technology	Cat5/5e; Cat6; Multimode
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>