

8-Port 2.5 Gbps Desktop Gigabit Ethernet Unmanaged Switch with PoE+ Pass-Through, 100W, Metal Enclosure, TAA

MODEL NUMBER: NG8POE-M2



Provides a 2.5 Gb Ethernet connection and power for PoE devices in your small office network or workgroup.

Features

8-Port Unmanaged 2.5 Gigabit Ethernet Switch for Home Offices and Workgroups

The energy-efficient NG8POE-M2 network switch connects up to eight devices to a Gigabit Ethernet network and allows them to communicate with each other. It's recommended for your home network, small office, workgroup or creative production environment. It helps you share large bandwidth-intensive files, such as CAD drawings and videos, at 2.5 Gigabit (2.5 Gbps) speeds, improving efficiency and cutting costly downtime.

Maximum Network Functionality

The NG8POE-M2 features eight twisted-pair RJ45 Gigabit Ethernet ports that support auto-negotiable 2.5 Gbps and auto MDI/MDIX functionality, so crossover cables and uplink ports are not needed for connections to PCs, routers and other switches. No configuration is required, so you can have your Gigabit network up and running immediately. IEEE 802.3x flow control (full duplex), back pressure (half duplex) and 60 Gbps switching capacity allow smooth transmission of large files. One 10 Gbps SFP+ port is included for uplinking data to other switches using optical fiber cabling.

Supports Power over Ethernet to Save You Money and Give You More Installation Choices

Because this network switch supports PoE, it can supply the power to operate compatible PoE devices, such as wireless LAN access points and bridges, VoIP phones and IP video cameras. This saves you the expense and effort of purchasing, connecting and installing individual power supplies for each device. It also helps you install PoE devices in areas far away from AC outlets, such as poles or ceilings. Eight RJ45 ports support up to 30W each with a total PoE budget of 100W when using the included AC power adapter.

Complies with IEEE Energy Efficient Ethernet Standards

The NG8POE-M2 supports IEEE 802.3az Energy Efficient Ethernet standards by automatically shifting unused ports into a low-power state without interrupting network connections. It also meets IEEE 802.3ab, 802.3i and 802.3u standards.

Plug-and-Play Functionality for Easy Use

No configuration is required in setting up the unmanaged NG8POE-M2, so you can have your 2.5 Gbps network up and running immediately. Cat5/5e/6/6a UTP/STP cables (sold separately) provide optimal performance. Easy-to-read LEDs indicate connection and activity status for each port. The NG8POE-M2

Highlights

- Capable of 2.5 Gb Ethernet network speeds ideal for high-bandwidth applications
- Supports PoE to save you expense and effort of powering PoE devices individually
- 8 twisted-pair auto-negotiable RJ45 ports support auto MDI/MDIX functionality
- Unused ports shift into low-power state without interrupting network connection
- IEEE friendly: supports 802.3az Energy Efficient Ethernet standards

Package Includes

- NG8POE-M2 8-Port 2.5 Gb Unmanaged Switch
- External power supply
- NEMA 5-15P to C13 power cord, 5 ft. (1.5 m)
- Schuko to C13 power cord, 5 ft. (1.5 m)
- Rubber mounting feet
- Owner's manual



Powering Business Worldwide

TRIPP LITE
SERIES

supports MAC address auto-learning and auto-aging for efficient routing.

Heavy-Duty Metal Enclosure with Versatile Installation Options

This plug-and-play switch comes with an external power supply and two detachable power cords: NEMA 5-15P and Schuko. Both power cords connect to the power supply's C14 inlet. The housing contains no fan, resulting in silent operation. The NG8POE-M2 is designed for desktop placement, but also features keyhole tabs for optional wall mounting.

Specifications

OVERVIEW	
UPC Code	037332287205
Product Type	Unmanaged Network Switch
INPUT	
Electrical Consumption (Max)	120W
AC Power Adapter Input Specs (V / Hz / A)	100-240V AC-, 50/60Hz
Electrical Consumption (Max PoE Load)	100W
Voltage Compatibility (VAC)	100-240
Input Frequency	50/60 Hz
Input Plug Type	NEMA 5-15P; Schuko
Input Cord Length (ft.)	5
Input Cord Length (m)	1.52
Power Source	AC Adapter with detachable power cord
POWER	
Power Consumption (Watts)	120.00
Output Volt/Amp (from external power supply)	55VDC, 2.22A
CONNECTIONS	
Number of Ports	9
Ports	9
Ports Detail	(x8) 2.5Gigabit RJ45 Ethernet Ports
SFP Uplink Ports	1
SFP Uplink Ports Detail	(x1) 10Gb SFP+ port
PoE Capability	30W (802.3at)
PoE Power Budget (Watts)	100
PoE Port Description	Alert: 90W; Budget: 100W. Maximum output :30W per each port



Powering Business Worldwide

TRIPP LITE
SERIES

PoE Supported Ports	8
Network Switch Ports	(8) 10/100/1000 (RJ45); (1) Dedicated SFP
PoE Type	Type 2 PoE+ (30W, IEEE 802.3at)
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	(x1 Green)PWR, (x8 Green) PoE, (x1 Green) PoE/MAX , (x8 Amber) 1-8 100M/1000M Link, (x8 Green) 2.5G Link, (x1 Blue) 10Gb SFP+ Uplink
PHYSICAL	
Primary Form Factor	Desktop; Wall-mount
Color	Black
Material of Construction	Metal
Form Factors Supported	Desktop, Wall mount
Shipping Dimensions (hwd / in.)	3.07 x 10.08 x 4.13
Shipping Dimensions (hwd / cm)	7.80 x 25.60 x 10.49
Shipping Weight (lbs.)	3.22
Shipping Weight (kg)	1.46
Unit Dimensions (hwd / in.)	1.060 x 9.450 x 4.130
Unit Dimensions (hwd / cm)	2.59 x 16.00 x 11.00
Unit Weight (lbs.)	1.1
Unit Weight (kg)	0.50
ENVIRONMENTAL	
Operating Temperature Range	0° to 104°F (0° to 40)
Storage Temperature Range	-40° to 158°F (-40° to 70°C)
Relative Humidity	5% - 90%, RH (Non-condensing)
Storage Humidity Range	5% - 90%, RH (Non-condensing)
COMMUNICATIONS	
Network Compatibility	100 Mbps (Fast Ethernet); 1 Gbps (Gigabit); 2.5 Gbps
Network Compatibility Details	Auto-negotiable
Switching Capacity	60Gbps
Switching Capacity Details	5Gbps per port with full duplex
FEATURES & SPECIFICATIONS	
Jumbo Frames	12000
Console Port	No
MAC Auto Learning	No



Powering Business Worldwide

TRIPP LITE
SERIES

MAC Addresses	4000
RMON	No
SNMP	No
Storm Control	No
DHCP Snooping	No
Auto MDI/MDIX Crossover Detection	No
Fans (Type/Quantity)	Fanless
STANDARDS & COMPLIANCE	
Product Certifications	EN 55032; EN 55035; NOM (Mexico)
Product Compliance	CE (Europe); FCC Part 15 Class B (USA); IEEE 802.3ab 1000Base-T; IEEE 802.3af PoE; IEEE 802.3at PoE+; IEEE 802.3az (Energy Efficient Ethernet); IEEE 802.3bt PoE++; IEEE 802.3u 100Base-TX/FX; IEEE 802.3x Flow Control; RoHS; Trade Agreements Act (TAA); UKCA
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://triplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.