



# Heavy-Duty Power Extension Cord, 15A, 14AWG (Right Angle IEC-320-C14 to IEC-320-C13), 2-ft.

MODEL NUMBER: P005-002-14RA







#### **Highlights**

- 2 ft. C13 to Right-Angle C14 Power Cord
- 14 AWG x 3C, 15A, 100-250V, SJT
- UL Listed

### Package Includes

 P005-002-14RA C13 to Right-Angle C14 Power Cord

Save space in tight places with this right-angle connector cord

#### **Description**

Use Tripp Lite's P005-002-14RA in server applications that require a higher rated, heavier gauge cable, and in which space is in high demand. The right-angle C14 connector on this power cord is perfect for saving space in tight areas, such as in the back of your rack enclosure cabinet. When plugged in, it seats flush against the back of a device (e.g. PDU, UPS, etc.), providing space for your rack door to close, or additional room to organize a tight area. C13 to Right-Angle C14 connectors, 3 x 14 AWG conductors, 15A rating, 100-250V, SJT jacket. Tripp Lite Lifetime Limited Warranty.

#### **Features**

- Molded, Heavy-Duty Power Cable, 2 ft.
- IEC-60320-C13 to Right-Angle IEC-60320-C14 connectors
- Right-angle C14 connector is perfect for saving space in tight areas
- 14 AWG x 3C, 15A, 100-250V, SJT jacket
- RoHS Compliant
- UL Listed

## **Specifications**

OVERVIEW	
UPC Code	037332179913
CONNECTIONS	
Side A - Connector 1	IEC-320-C14 - RIGHT ANGLE
Side B - Connector 1	IEC-320-C13





PHYSICAL		
Color	Black	
Power Cord Jacket Type	SJT	
Wire Gauge (AWG)	14	
Cable Length (ft.)	2	
Cable Length (m)	0.61	
Shipping Dimensions (hwd / in.)	10.00 x 7.00 x 0.10	
Shipping Dimensions (hwd / cm)	25.40 x 17.78 x 0.25	
Shipping Weight (lbs.)	0.31	
Shipping Weight (kg)	0.14	
ENVIRONMENTAL		
Operating Temperature Range	-4 F (-20 C) to 140 F (60 C)	
Storage Temperature Range	-4 F (-20 C) to 140 F (60 C)	
Operating Humidity Range	10-85% RH	
Storage Humidity Range	10-85% RH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.