

## UK Computer Power Cord - BS1363 to C5, 2.5A, 250V, H03VV-F, 6 ft. (1.83 m), Black

MODEL NUMBER: P060-02M-UK



Connects a notebook computer or laptop with a 3-slot C6 power inlet to a PDU or UPS system with BS 1363 outlets.

### Features

#### European Computer Power Cord Connects Notebook Computers to a BS 1363 AC Outlet

This VDE-compliant power cable connects a notebook computer, laptop or other device with a three-slot C6 inlet to a PDU, UPS or surge protector with BS 1363 outlets. The P060-02M-UK features a BS 1363 end for connecting to an AC power source and an IEC-320-C5 end for connecting to devices.

#### H03VV-F Jacket Is Fully VDE-Compatible for European Applications

The 0.75mm<sup>2</sup> enhanced PVC jacket complies with VDE, CE and UKCA standards for data centers, racks, workstations and other IT applications in Europe.

### Highlights

- Recommended for powering notebook computers and laptops with C6 inlets
- Ideal replacement for a worn-out or missing laptop adapter power cable
- VDE-compliant H03VV-F jacket allows use in European IT applications

### Package Includes

P060-02M-UK C5 to BS 1363 Computer Power Cable, 6 ft. (1.8 m), Black

## Specifications

OVERVIEW	
UPC Code	037332281081
Product Type	Computer Power Cord
Device Compatibility	Laptop; Monitor/HDTV
Country/Region	UK
INPUT	
Maximum Input Amps	2.5
Voltage Compatibility (VAC)	250
PHYSICAL	

Plug Color	Black
Cable Jacket Color	Black
Cable Jacket Material	PVC
Power Cord Jacket Type	H03VV-F
Cable Outer Diameter (OD)	5.9 mm
Number of Conductors	3
Conductor Gauge	24/0.20AS
Wire Gauge (AWG)	18
Wire Gauge (OD - mm <sup>2</sup> )	0.75
Power Cord Color	Black
Cable Length (ft.)	6.56
Cable Length (m)	2.00
Shipping Dimensions (hwd / in.)	9.01 x 7.01 x 0.50
Shipping Dimensions (hwd / cm)	22.89 x 17.81 x 1.27
Shipping Weight (lbs.)	0.43
Shipping Weight (kg)	0.20
Unit Dimensions (hwd / in.)	9.010 x 7.010 x 0.500
Unit Packaging Type	Polybag
Unit Weight (lbs.)	0.410
Unit Weight (kg)	0.19
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	5° to 158°F (-15° to 70°C)
Storage Temperature Range	5° to 140°F (-15° to 60°C)
Operating Humidity Range	20% TO 80% RH, NON-CONDENSING
Storage Humidity Range	20% TO 80% RH, NON-CONDENSING
<b>CONNECTIONS</b>	
Side A - Connector 1	BS1363 UK PLUG
Side B - Connector 1	IEC-320-C5
<b>FEATURES &amp; SPECIFICATIONS</b>	
Antibacterial	No
Armored Cable	No
Angled Plug	No
High Voltage	Yes

# TRIPP-LITE

by **EAT•N**

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

Locking Plug	No
Coiled Power Cord	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	CE (Europe); REACH; RoHS; UKCA
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

# TRIPP-LITE

by **EAT•N**

© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.