



Powering Business Worldwide

## SCSI Ultra2/U160/U320 LVD Cable (HD68 M/M), 10-ft.

MODEL NUMBER: **S450-010**



### Highlights

- Premium double-shielded cable
- Meets the most current SCSI specifications for high-speed devices

### System Requirements

- Any external SCSI device or host controller card requiring HD68 interface

### Package Includes

- 10-ft. SCSI U2/U160/U320 LVD/SE cable HD68M to HD68M w/thumb screws

### Description

Multi-platform SCSI III external peripheral cable HD68M/M. This 10ft cable is designed to connect two SCSI III (fast and wide) or SCSI II devices together. Supports all legacy transfer rates through Ultra 320. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

### Features

- Backwards compatibility with previous SCSI generations
- Supports all SCSI transfer rates through 320/mb/s
- LVD/SE compliant
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

## Specifications

OVERVIEW	
UPC Code	037332121318
Technology	SCSI
CONNECTIONS	
Side A - Connector 1	HD68 (MALE)
Side B - Connector 1	HD68 (MALE)

PHYSICAL	
Color	Black
Cable Length (ft.)	10
Cable Length (m)	3.05
Shipping Dimensions (hwd / in.)	14.00 x 13.00 x 2.00
Shipping Dimensions (hwd / cm)	35.56 x 33.02 x 5.08
Shipping Weight (lbs.)	1.00
Shipping Weight (kg)	0.45
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.