

## 1440VA 1000W 120V Line-Interactive Cloud-Connected UPS with Remote Monitoring - 10 NEMA 5-15R Outlets (5 Surge + 5 Surge and Battery Backup), Extended Run, LCD, 5-15P Plug, Tower

MODEL NUMBER: **SMART1500LCDTXC**



The Line Interactive UPS, featuring a sleek tower design, offers reliable protection for your devices against brownouts, surges, and power interruptions. Its user-friendly LCD interface, coupled with advanced cloud monitoring capabilities, ensures convenient monitoring of your power supply, both on-site and remotely.

### Features

#### 1.4kVA/1kW/120V Battery Backup for Network and Retail Point-of-Sale Applications

The SMART1500LCDTXC Line-Interactive cloud-connected UPS system regulates incoming voltage and provides reliable battery backup and AC power protection against blackouts, brownouts, overvoltages, surges, and Line noise. Its compact tower form factor is suitable for desktop, floor placement, under workstations and other locations where a taller "Rack/Tower" unit may not fit. It's recommended for Home/office, Point-of-sale workstations, digital signage equipment, and gaming equipment.

#### Easy-to-Use Cloud-Enabled Remote Monitoring Powered by Brightlayer

Eaton's cloud-based remote monitoring app offers convenient setup, control and management of a single UPS or a larger deployment. Scan the QR code on the UPS to download the app to your mobile device. Receive alerts, push configurations, silence alarms or control load banks using a mobile app or web browser. Being able to monitor and access multiple UPS systems from a remote location helps reduce the number of site visits, saving you time and money. The unit's NFC (Near-Field Communication) feature lets you configure network settings instantly from your mobile device.

#### Allows Time to Back Up Critical Files During a Blackout

During short blackouts, the SMART1500LCDTXC switches to battery power to keep connected equipment running. This allows you enough time to save data and complete a safe shutdown in case of a longer outage. Once AC power is restored, the SMART1500LCDTXC restarts automatically, regardless of battery charge level, saving you a costly site visit.

#### NEMA 5-15R Outlets and Controllable Load Banks Protect Connected Components

Five 5-15R outlets provide battery backup and surge protection for your computer, monitor, security camera and other crucial equipment. The other five 5-15R outlets provide surge suppression only for desk lamps, speakers and other equipment regarded as non-essential during a blackout. Eaton's remote monitoring application enables individual control of two switchable load banks, allowing them to be powered on, off, or cycled remotely. This remote functionality facilitates the rebooting of equipment that is not responding, thereby eliminating the need for expensive and time-consuming on-site visit.

### Highlights

- Cloud-based dashboard allows 24/7 remote monitoring via browser or mobile app
- Cloud-connected UPS sets up in minutes to start protecting your devices
- Create account with two-factor authentication for an additional layer of security
- NFC technology allows easy configuration of network settings from your mobile device
- Add external battery module (sold separately) to extend runtime during power outages
- Auto-restart with input power, regardless of the battery's low charge or if its completely absent

### Package Includes

- SMART1500LCDTXC 1440VA 1000W 120V Cloud-Connected Line-Interactive UPS
- Quick Start Guide



Powering Business Worldwide

TRIPP LITE  
SERIES

**Automatic Voltage Regulation (AVR) Corrects Low- and High-Voltage Conditions**

AVR protects your equipment from incremental hardware damage, data loss and performance problems caused by brownouts and overvoltages. The SMART1500LCDTXC can correct brownouts as low as 92V and overvoltages as high as 150V back to nominal 120V power continuously, all while keeping the battery fully charged and ready to take over in case of power failure.

**Easy Preventative Maintenance and Initial Troubleshooting**

The SMART1500LCDTXC's self-test capability and user-replaceable internal battery can extend the life of the UPS and minimize disruption to operations. A resettable circuit breaker on the rear of the UPS helps prevent dangerous system overloads.

**Intuitive LCD, Home-Friendly Alarm and Diagnostic LEDs Keep You Informed 24/7**

The easy-to-read LCD and two diagnostic LEDs provide vital status information, including voltage, battery level, load level and power usage. The audible alarm indicates low-battery and fault conditions. It can be disabled via the LCD or the remote monitoring app, which will still respond to silenced alarms via the app.

**Communications Ports**

The UPS features an RJ45 port for Ethernet connectivity, enabling the use of a cloud-based remote monitoring application. Additionally, a USB-C port is provided for direct connection to the UPS's Command Line Interface (CLI), facilitating the configuration and identification of local network parameters.

**Extendable Runtime via Optional External Battery Module**

By adding (optional BP24V15RT2U) External Battery Module, the on-battery runtime of the SMART1500LCDTXC can be significantly increased. This enhancement enables the UPS to sustain power over extended periods of outages, thereby providing additional runtime for heavier loads. External Battery Module limit to one per UPS unit.

## Specifications

OVERVIEW	
UPC Code	037332281340
UPS Type	Line-Interactive
INPUT	
Input Phase	Single-Phase
Rated input current (Maximum Load)	12A
Nominal Input Voltage(s) Supported	120V AC
UPS Input Connection Type	5-15P
Input Circuit Breakers	15A
UPS Input Cord Length (ft.)	5
UPS Input Cord Length (m)	1.5
Recommended Electrical Service	15A 120V
Maximum Input Amps	12
Input Frequency	50/60Hz
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	5
Input Cord Length (m)	1.52

OUTPUT	
Output Capacity (VA)	1440
Output Capacity (kVA)	1.5
Output Capacity (Watts)	1000
Output Capacity (kW)	1
Power Factor	0.69
Nominal Voltage Details	120v nominal output in battery mode
Frequency Compatibility	50 / 60 Hz
Output Voltage Regulation (Line Mode)	120V (+15%/-18%)
Output Voltage Regulation (Battery Mode)	120V (±10%)
UPS Output Receptacles (Surge Suppression Only)	5 UPS outlets, 5 surge-only outlets
Output AC Waveform (AC Mode)	Pure sine wave
Output (Watts)	1000
Output AC Waveform (Battery Mode)	PWM sine wave
Nominal Output Voltage(s) Supported	110V; 115V; 120V
Output Receptacles	(10) 5-15R
Overload Protection	110%±10%,GOES TO FAULT AFTER 5MIN (Line Mode), 120%±10%,GOES TO FAULT IMMEDIATELY (Line Mode); 110%±10%,SHUTS DOWN IN 5 SEC (Battery Mode), 120%±10%, SHUTS DOWN IMMEDIATELY (Battery Mode)
Customized Load Management Receptacles	2 Load Banks: Load bank 1: 2 outlets, Load bank 2: 2 outlets
Individually Controllable Load Banks	Yes
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Runtime Full Load (min.)	2 min. (1000W)
Runtime Half Load (min.)	10 min. (500W)
Expandable Runtime	Yes
Expandable Battery Runtime	Extended runtime supported via optional Tripp Lite Series 24VDC <a href="https://tripplite.eaton.com/External-24V-2U-Rack-Tower-Battery-Pack-for-select-Tripp-Lite-UPS-Systems~BP24V15RT2U">BP24V15RT2U</a> external battery packs
Expandable Runtime Description	<a href="https://tripplite.eaton.com/External-24V-2U-Rack-Tower-Battery-Pack-for-select-Tripp-Lite-UPS-Systems~BP24V15RT2U">BP24V15RT2U</a> ; (limit 1)
External Battery Pack Compatibility	<a href="https://tripplite.eaton.com/External-24V-2U-Rack-Tower-Battery-Pack-for-select-Tripp-Lite-UPS-Systems~BP24V15RT2U">BP24V15RT2U</a> ; (limit 1)
DC System Voltage (VDC)	24
Battery Recharge Rate (Included Batteries)	8 hours (10% to 90%)



Powering Business Worldwide

TRIPP LITE  
SERIES

Battery Access	Battery access door
Battery Replacement Description	Replaceable internal batteries (see manual)
<b>VOLTAGE REGULATION</b>	
Voltage Regulation Description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 89 to 145
Overvoltage Correction	Input voltages between 132 and 145 are reduced by 15%
Undervoltage Correction	Input voltages between 89 and 108 are boosted by 18%
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Front Panel LCD Display	LCD screen with scroll buttons indicates Input voltage, Output voltage, Frequency (Hz), AVR boost / cut status, Output load in watts, Output load percentage, Battery voltage, and Estimated runtime in minutes.
Switches	Power off/on, Test, & Mute.
Alarm Cancel Operation	Power-fail alarm can be silenced via front LCD display or via Remote Monitoring Application
Audible Alarm	UPS remains silent in battery backup mode; Alarm sounds only to report low-battery, fault, overload and replace-battery conditions
LED Indicators	Green Solid: Running on AC power, Battery Fully Charged. Green Flashing: Running on AC power, Battery charging. Red: Fault
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC Suppression Joule Rating	380
UPS AC Suppression Response Time	Instantaneous
EMI / RFI AC Noise Suppression	Yes
<b>PHYSICAL</b>	
Primary Form Factor	Tower
Rack Height	0U
Cooling Method	Fan
Installation Form Factors Supported with Included Accessories	Tower
Primary UPS Depth (mm)	370
Primary UPS Height (mm)	200
Primary UPS Width (mm)	150
Shipping Dimensions (hwd / in.)	11.69 x 9.25 x 19.48
Shipping Weight (lbs.)	30.86
Shipping Weight (kg)	14.00
UPS Housing Material	ABS
UPS Power Module Dimensions (hwd, in.)	7.874 x 5.906 x 14.567
UPS Power Module Weight (kg)	13.00
UPS Power Module Weight (lbs.)	28.660



Powering Business Worldwide

TRIPP LITE  
SERIES

Unit Dimensions (hwd / in.)	7.874 x 5.906 x 14.567
Unit Weight (lbs.)	28.660
Unit Weight (kg)	13.00
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	5° to 122°F (-15° to 50°C)
Relative Humidity	0 to 90%, non-condensing
AC Mode BTU / Hr. (Full Load)	57.72
AC Mode Efficiency Rating (100% Load)	98.4%
Audible Noise	45dB @ 1m front side
<b>COMMUNICATIONS</b>	
Network Management Card Description	Cloud-enabled network management interface powered by Eaton Brightlayer Remote Monitoring Application.
Communications Interface	Near Field Communication (NFC); RJ45 Network; USB-C
<b>LINE / BATTERY TRANSFER</b>	
Transfer Time	4 milliseconds typical (10 milliseconds max)
Low Voltage Transfer to Battery Power (Setpoint)	89
High Voltage Transfer to Battery Power (Setpoint)	145
<b>FEATURES &amp; SPECIFICATIONS</b>	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
High Availability UPS Features	Automatic Voltage Regulation (AVR); Expandable battery backup; Remote management; Surge/noise protection
Green Energy-Saving Features	Greater than 95% efficiency - GREEN UPS
<b>APPLICATIONS</b>	
UPS Applications	Home/Office Desktop; Audio/Video; High-End Desktop/Small Network; Retail/Point of Sale; Hospitality
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CSA (Canada); ICES (Canada); NOM (Mexico); RETIE (Colombia); UL 1778
Product Compliance	ENERGY STAR Qualified; FCC Part 15 Class B (USA); RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (U.S. & Canada)	3-year limited warranty
Product Warranty Period (Latin America)	3-year limited warranty



Powering Business Worldwide

TRIPP LITE  
SERIES

Product Warranty Period (Mexico)	3-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 &nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> &nbsp;

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.