

Important Note

Power Strips used within the Patient Care Vicinity, may be permanently attached by a means such that it is only removable with the use of a tool. Choose the PSCLAMP for a safe & secure mounting solution.

Safe-IT UL 60601-1 Medical-Grade Surge Protector for Patient-Care Vicinity, 4x Hospital-Grade Outlets, 15 ft. Cord, Antimicrobial Protection

MODEL NUMBER: SPS415HGULTRA



Full 60601-1 compliance and agency listing, surge protection, integrated locking safety covers and a 15 ft. cord make this medical-grade power strip ideal for standalone use inside and outside patient-care vicinities.

Description

The SPS415HGULTRA Medical-Grade Power Strip -- patent #7,375,939 and 8,339,759 -- is designed with full 60601-1 and 60950-1 compliance, making it ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas.

This 120V, 50/60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and four NEMA 5-15R-HG hospital-grade outlets that include integrated locking safety covers. Plus, 1410 joules of surge suppression prevent dangerous power spikes that can damage connected equipment and destroy data. A 15A resettable circuit breaker also protects your equipment from overloads. An LED indicator tells you power is present and protected from surges (with no ground faults or line/neutral reversals).

The power strip is protected by an antimicrobial powder coating. Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew. The coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

Mounting slots and flanges let you install the SPS415HGULTRA on a wide variety of surfaces. The all-metal housing ensures safety and is guaranteed to stand up to demanding environments.

With a switchless design that prevents accidental shutoff and a 15-foot (4.6-meter) power cord that provides flexibility in placing the power strip, the SPS415HGULTRA is a recommended replacement for all non-compliant power strips.

Features

Power Distribution Anywhere in Any Medical Facility Ideal for stand alone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas
120V, 50/60 Hz power strip complies with UL 60601-1 and UL 60950-1 specifications
Automatic site fault detection protects patients and staff
Tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 Canadian standards
Patent #7,375,939 & 8,339,759

Highlights

- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Approved for standalone use in all patient-care vicinities
- Listed to UL 60601-1 and UL 60950-1 specifications
- 1410 joules of surge suppression
- 4 NEMA 5-15R-HG hospital-grade outlets with locking safety covers

Package Includes

- SPS415HGULTRA UL 60601-1 Medical-Grade Power Strip
- Owner's manual



Powering Business Worldwide

TRIPP LITE
SERIES

Exclusive Antimicrobial ProtectionAntimicrobial coating helps resist the growth of bacteria, viruses, fungi, mold and mildewCoating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

Versatile Medical-Grade Solution4 NEMA 5-15R-HG hospital-grade outlets provide consistent power15-ft. (4.57 m) power cord with NEMA 5-15P-HG plug provides reach to the power sourceRugged all-metal housing for long life in demanding environments

Premium Safety Features1410 joules of surge suppression protect against dangerous power spikesIntegrated locking outlet safety covers block access to unused outletsBuilt-in 15A resettable circuit breaker protects against dangerous overloadsSwitchless design prevents accidental shut-offLED indicates power is present and surge-protected

Ready to Use Right Out of the BoxBuilt-in mounting slots and flanges for easy installation on a variety of surfaces

Specifications

OVERVIEW	
UPC Code	037332159236
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Voltage Compatibility (VAC)	120
Maximum Surge Amps	60000
Input Plug Type	NEMA 5-15P-HG
Input Cord Length (ft.)	15
Right-Angle Plug	No
Input Cord Length (m)	4.57
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(4) 5-15R-HG
Circuit Breaker (amps)	15
Overload Protection	15A resettable circuit breaker
Outlet Orientation	Single row of 4
Right-Angle Outlets	No
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes



Powering Business Worldwide

TRIPP LITE
SERIES

LED Indicators	Proper wiring and surge protection working
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1410
Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	No
PHYSICAL	
Material of Construction	Metal
Power Cord Color	White
Housing Color	White
Mounting Holes or Slots	Yes
Receptacle Color	White
Shipping Dimensions (hwd / in.)	14.17 x 5.98 x 2.17
Shipping Dimensions (hwd / cm)	35.99 x 15.19 x 5.51
Shipping Weight (lbs.)	3.51
Shipping Weight (kg)	1.59
Unit Dimensions (hwd / in.)	1.500 x 13.750 x 2.500
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4
Unit Weight (lbs.)	3.20
Unit Weight (kg)	1.45
Mounting Details	Includes flanges
FEATURES & SPECIFICATIONS	
Rotatable Outlets	No
Antimicrobial	Yes
Mounting Accessory Included	Yes
Antibacterial	No
STANDARDS & COMPLIANCE	
Patented	Patent# 7,375,939; Patent# 8,339,759
Product Certifications	CSA (Canada); CAN/CSA-C22.2 No. 601.1; CAN/CSA-C22.2 No. 601.1-M90 (Canada); CAN/CSA-C22.2 No. 60950-1 (Canada); UL 60950-1; UL 1363; UL 60601-1
Product Compliance	RoHS



Powering Business Worldwide

TRIPP LITE
SERIES

WARRANTY & SUPPORT

Product Warranty Period (Worldwide)	Lifetime limited warranty
--	---------------------------

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.