


Frame End Kit for Hot/Cold Aisle Containment System

MODEL NUMBER: SRCTMTFRM



Aisle Containment System keeps hot and cool air separated for better temperature control and equipment performance in hot aisle/cold aisle configurations.

Features

Heavy-Duty Steel Frame Supports Tripp Lite's Aisle Containment System Two SmartRack® frame kits are required to create a semi-airtight aisle that keeps cold and hot air separated to increase efficiency in temperature control and distribution among the racks. The SRCTMTFRM must also be paired with Tripp Lite's SRCTMTTLBM Beam Kit and SRCTMTSDD Sliding Double-Door Kit (both sold separately). Note: the Aisle Containment System can be configured to be a self-standing unit (tied to racks on both ends) or can be tied directly to a wall at the end of an aisle, no longer needing a second SRCTMTSDD to seal the end.

Accommodates Various Server Rack Heights from 42U to 48U The steel frame with black powder-coated finish features pre-drilled mounting holes for the telescopic beam kit (SRCTMTTLBM), making installation efficient and effective, and pre-tapped holes for further fortification. Stabilizing brackets are provided at both feet, allowing the frame to be directly affixed to the floor of your data center. All necessary hardware is included for assembly. Multiple frame kits may be connected together for larger containment arrays.

Tripp Lite's Aisle Containment System Manages Airflow for More Cooling Efficiency Upon installation in your data center or server room, the modular, easy-to-assemble Aisle Containment System contains the air in a hot aisle or cold aisle, essentially creating a room within the aisle, while still keeping the aisle accessible. No costly contractor or HVAC specialist is required to install the system, which can be expanded or adapted to meet your needs. Assorted frame kits, beam kits, sliding double-door kits, roof panel kits and adapter riser panel kits (all sold separately) are necessary to assemble a hot or cold Aisle Containment System that accommodates the dimensions of your aisle and the rack enclosures within it.

Highlights

- Supports beams and sliding doors as foundation of Tripp Lite aisle containment system
- Constructed from heavy-duty steel covered with a black powder-coated finish
- Features pre-drilled mounting holes for efficient connection to telescopic beam kit
- Stabilizing brackets allow permanent connection to your data center's floor
- Minor assembly required using the included hardware

Applications

- Provide a semi-airtight seal to prevent hot and cold air from mixing within a contained aisle in your data center or server room

System Requirements

- SRCTMTTLBM Beam Kit
- SRCTMTSDD Sliding Double-Door Kit
- SRCTMTCVR600 or SRCTMTCVR750 Static Roof Panel Kit
- SRCTMTR600SH, SRCTMTR600TL, SRCTMTR750SH or SRCTMTR750TL Adapter Riser Panels

Package Includes

- (2) Frame uprights
- (2) Frame crossbars
- Outer aisle endcap



- Inner aisle endcap
- Temporary frame support bracket
- (4) Floor mounting brackets
- (4) Crossbeam connection brackets
- (2) Horizontal endcap mounting brackets
- (4) Vertical endcap mounting brackets
- (2) Sliding door adjustment brackets
- (4) M5 x 10 Phillips screws
- (76) M6 x 16 Phillips screws
- (8) M8 x 20 Phillips screws
- (48) M6 external tooth lock washers
- (8) M8 external tooth lock washers
- Installation guide

Specifications

OVERVIEW	
UPC Code	037332240279
Aisle Containment System Component Type	Frame Kit
PHYSICAL	
Color	Black
Shipping Weight (kg)	56.47
Unit Dimensions (hwd / cm)	199,39 x 60,02 x 109,22
Unit Dimensions (hwd / in.)	78.5 x 23.63 x 43
Unit Weight (kg)	127.46
Unit Weight (lbs.)	281
Rack Compatibility	600 mm (Standard); 750 mm (Wide)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

SPECIAL FEATURES	
Built-in Cable Management	Yes
STANDARDS & COMPLIANCE	
Approvals	EIA/ECA-310-E
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>