

USB-C Dock - 4K HDMI, USB 3.2 Gen 1, USB-A/C Hub, GbE, Memory Card, 60W PD Charging

MODEL NUMBER: U442-DOCK11-S



USB-C dock with PD Charging adds 4K HDMI, USB-A, USB-C and Ethernet ports to your laptop or tablet's USB-C or Thunderbolt 3 port.

Features

USB-C Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a Workstation This multiport USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, tablet or other device with a USB-C or Thunderbolt 3 port. It's ideal for connecting to a wired Gigabit Ethernet network, transmitting digital audio and video to a large display, adding a thumb drive or other USB peripheral, powering and charging a PD Charging-compliant mobile device and more—all at the same time.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video Signals By connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K Video and Digital Audio The HDMI port supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. A DVI display may also be connected using an HDMI to DVI adapter (sold separately). HDCP 2.2 compliance allows you to stream 4K Amazon and Netflix content with no complications.

Accesses a Wired Gigabit Ethernet Network The RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

USB Ports Connect Keyboards, Thumb Drives and Other USB Peripherals Two USB 3.2 Gen 1 ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support fast data transfer rates up to 5 Gbps and are backward compatible with USB 2.0 and USB 1.1 devices. Note: Host must support USB OTG (On-the-Go).

PD 2.0 Charging Port Charges Connected Device via AC Wall Charger The USB-C Power Delivery port supports power output up to 20V 3A (60W), which is sufficient for charging and powering the connected source device, such as an Android smartphone or Chromebook. Just connect the device's AC wall charger to the USB-C PD port. This port can also be used for transferring data up to 5 Gbps. Note: USB-C PD port does not support Quick Charge (QC).

Allows External Memory Access Memory card slots support Micro SD and SD/MMC cards for transferring data to and from your connected computer, laptop or tablet. Both memory card slots can be used at the same time.

Built-In USB-C Cable Connects in Either Direction Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the Package The plug-and-play USB-C dock is specifically designed for use with Windows laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed. The compact unit fits

Highlights

- Transmits audio/video signals from sources supporting USB DisplayPort Alt Mode
- Supports Ultra HD 4K resolutions up to 3840 x 2160 @ 30 Hz for crystal-clear video
- Joins a wired 10/100/1000 Gigabit Ethernet network when no Wi-Fi is available
- Supports 20V 3A (60W) power output for fast-charging compatible mobile devices
- USB-C, USB-A and memory card ports allow connection of flash drives and other peripherals

Applications

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Transfer data to and from a USB flash drive or memory card
- Connect a microphone/headset to record a podcast or listen to music

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode



easily into a pocket, briefcase or laptop bag for connecting on the go. If additional power is required, the 5V DC power jack is compatible with power supplies (not included) equipped with a 3.5 x 1.35 x 9.5 millimeter output plug, a positive tip and a negative sleeve.

- Display device with HDMI or DVI* input
 - Not for use with Thunderbolt monitors
- *Requires adapter (sold separately)

Package Includes

- U442-DOCK11-S USB-C Dock, Silver
- Owner's manual

Specifications

| OVERVIEW | |
|--------------------------------|--|
| UPC Code | 037332213372 |
| Product Type | Docking Station |
| Technology | HDMI; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1); PD Charging |
| Host Connector | USB C (MALE) |
| VIDEO | |
| Number of Monitors Supported | 1 |
| Video Ports | HDMI (FEMALE) |
| Video Ports Detail | HDMI 2.0; HDCP 2.2 |
| Resolutions Supported | HDMI: 4K 30Hz (3840 x 2160) |
| Max Supported Video Resolution | HDMI: 3840 X 2160 (4K X 2K) @ 30HZ |
| Extended Mode | No |
| Mirror Mode | No |
| Max Supported Color Depth | 24-bit True Color |
| Chroma Sub Sampling | 4:4:4 |
| DATA | |
| Data Ports | (1) USB C (FEMALE); (2) USB A (FEMALE) |
| Data Ports Detail | (1) USB-C - USB 3.2 Gen 1 (5 Gbps); (2) USB-A - USB 3.2 Gen 1 (5 Gbps) |
| NETWORK | |
| Network Ports | RJ45 (FEMALE) |



| STORAGE | |
|---|---|
| Card Slots | SD (FEMALE); MICRO SD (FEMALE) |
| Card Slots Detail | Both card readers can be used at the same time |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| Built-In Cable Length (ft.) | 0.49 |
| Built-In Cable Length (m) | 0.15 |
| Built-In Cable Length (in.) | 5.9 |
| Built-In Cable Length (cm) | 15 |
| Bus Powered | Yes |
| Product Length (in.) | 12 |
| Product Length (cm.) | 30.48 |
| Product Length (ft.) | 1 |
| Product Length (m.) | 0.3 |
| BATTERY | |
| Battery Charging (5V/1.5A Port) | No |
| POWER | |
| External Power Supply Output Specs (V / A) | 5V/2A |
| External Power Supply DC Barrel Connector Specs | OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve |
| USB Power Delivery (PD) Charging Support | Yes |
| USB Power Delivery (PD) Charging Specification | 2.0 |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | White (Power), Green (Link), Yellow (Activity) |
| CHARGING | |
| Charging Ports / Amps | (2) 0.9A; 3A |
| Charging Ports | USB-C: 60W (20V 3A) Power Delivery (PD 2.0) |
| Total Charging Watts | 60 |
| PHYSICAL | |
| Cable Jacket Rating | VW-1 |



| | |
|---------------------------------------|---|
| Color | Silver; White |
| Material of Construction | Aluminium |
| Shipping Dimensions (hwd / in.) | 0.80 x 5.70 x 3.20 |
| Shipping Weight (lbs.) | 0.30 |
| Unit Dimensions (hwd / in.) | 0.67 x 4.7 x 2.2 |
| Unit Packaging Type | Box |
| Unit Weight (kg) | 0.10 |
| Unit Weight (lbs.) | 0.21 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 131 F (0 to 55 C) |
| Storage Temperature Range | 14 to 158 F (-10 to 70 C) |
| Relative Humidity | 5% to 95% RH, Non-Condensing |
| BTUs | 15.7 BTU/Hr |
| Power Consumption (Watts) | 4.6 |
| Power Provided to Connected Device(s) | 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) |
| COMMUNICATIONS | |
| Network Speed | Gigabit Ethernet (10/100/1000) |
| IEEE Standards Supported | 802.3 |
| CONNECTIONS | |
| Ports | 8 |
| Dock Connectors | 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA |
| Side A - Connector 1 | USB C (MALE) |
| Side B - Connector 1 | HDMI (FEMALE); RJ45 (FEMALE) |
| Side B - Connector 2 | (2) USB 3.0 A (FEMALE) |
| Side B - Connector 3 | MICRO SD (FEMALE) |
| Side B - Connector 4 | SD (FEMALE) |
| Side B - Connector 5 | USB Type-C (FEMALE) |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| HDMI Specification | 2.0 |
| HDCP Specification | 2.2 |
| USB Hub Ports | Yes |



| | |
|-------------------------------------|--|
| Number of USB Hub Ports | 2 |
| USB Specification | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) |
| Driver Required | No |
| Recommended Category Cable | Cat5/5e/6 Cables |
| Auto MDIX Support | Yes |
| Full Duplex Support | Yes |
| Suspend Mode Support | Yes |
| Remote Wakeup Support | Yes |
| SD Card Specification | SD; Micro SD |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to CE, FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>