

## 4-Port USB-C Hub, USB 3.x (5Gbps), 4x USB-A Ports, 60W PD Charging, White

MODEL NUMBER: **U460-004-4A-C**



Adds USB-A and USB-C PD charging ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

### Description

The U460-004-4A-C USB 3.1 Gen 1 USB-C Portable Hub expands the potential of your tablet, laptop, MacBook, Chromebook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for adding a thumb drive and other USB peripherals and powering and charging a PD Charging-compliant mobile device—all at the same time.

The plug-and-play U460-004-4A-C requires no software, drivers or external power. Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Four USB-A ports accept USB peripherals, such as a flash drive, mouse, keyboard or printer, and the dedicated fast-charging port provides up to 5V/1.5A (7.5W) for charging smartphones and other mobile devices. All ports support fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices.

The USB-C Power Delivery (PD) port provides power and charging to the PD Charging-compliant device (such as a MacBook or Chromebook) connected to the U460-004-4A-C. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 3A (60W).

### Features

#### Turn Your Device's USB-C Port into a Multiport Workstation

- Ideal for adding USB peripherals and powering and charging a PD Charging-compliant mobile device simultaneously
- Plug-and-play operation with no software, drivers or external power required
- About the size of a credit card for easy carrying in a pocket, purse or laptop bag

#### Connect USB Peripherals

- 4 USB-A ports accept flash drives, mice, keyboards, printers and other USB peripherals
- USB-A fast-charging port provides up to 5V/1.5A (7.5W) for charging mobile devices
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1

Note: Host must support USB OTG (On-the-Go)

#### Charge a Connected Device

- USB-C PD port connects to wall charger to power and charge the connected PD Charging-compliant USB-C/Thunderbolt 3 device

### Highlights

- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- USB-C PD charging port supports power input up to 20V 3A (60W)
- USB-A fast-charging port provides up to 5V/1.5A (7.5W) for charging devices
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required

### System Requirements

- Source device with USB-C or Thunderbolt 3 port

### Package Includes

- U460-004-4A-C USB 3.1 Gen 1 USB-C Portable Hub
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

- Supports power input up to 20V 3A (60W)

Note: USB-C PD port does not support Quick Charge (QC).

#### Built-In Cable with Reversible USB-C Connector

- Fumble-free reversible USB-C plug connects in either direction for quick connection every time

## Specifications

| OVERVIEW                                 |                        |
|--|------------------------|
| UPC Code                                 | 037332193773           |
| Technology                               | USB 3.x                |
| Host Connector                           | USB C (MALE)           |
| VIDEO                                    |                        |
| Extended Mode                            | No                     |
| Mirror Mode                              | No                     |
| DisplayPort Alt Mode                     | No                     |
| DATA                                     |                        |
| Data Ports                               | (4) USB A (FEMALE)     |
| INPUT                                    |                        |
| Bus Powered                              | Yes                    |
| Product Length (in.)                     | 6                      |
| Product Length (cm.)                     | 15.24                  |
| Product Length (ft.)                     | 0.5                    |
| Product Length (m)                       | 0.15                   |
| BATTERY                                  |                        |
| Battery Charging (5V/1.5A Port)          | Yes                    |
| POWER                                    |                        |
| Power Consumption (Watts)                | 2.2                    |
| USB Power Delivery (PD) Charging Support | Yes                    |
| CONNECTIONS                              |                        |
| Number of Ports                          | 5                      |
| Side A - Connector 1                     | USB C (MALE)           |
| Side B - Connector 1                     | (4) USB 3.0 A (FEMALE) |
| Side B - Connector 2                     | USB C (FEMALE)         |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                       |  |
|---------------------------------------|--|
| Connector Plating                     | Nickel   |
| <b>CHARGING</b>                       |  |
| Total Charging Watts                  | 60   |
| Charging Ports / Amps                 | 1.5A; 3A   |
| <b>PHYSICAL</b>                       |  |
| Color                                 | White  |
| Material of Construction              | Plastic  |
| Cable Jacket Rating                   | VW-1   |
| Shipping Dimensions (hwd / in.)       | 1.00 x 3.90 x 5.60   |
| Shipping Weight (lbs.)                | 0.15   |
| Unit Dimensions (hwd / in.)           | 0.000 x 0.000 x 0.000  |
| Unit Packaging Type                   | Box  |
| Unit Weight (lbs.)                    | 0.1  |
| Unit Weight (kg)                      | 0.05   |
| <b>ENVIRONMENTAL</b>                  |  |
| Operating Temperature Range           | 32° to 113°F (0° to 45°C)  |
| Storage Temperature Range             | 14° to 158°F (-10° to 70°C)  |
| Relative Humidity                     | 10% to 90% RH, Non-Condensing  |
| BTUs                                  | 7.5 BTU/Hr   |
| Power Provided to Connected Device(s) | Up to 20V 3A (60W) Input (USB-C), 5V 1.5A (7.5W) Output USB port, 5V 0.9A (4.5W) Output per USB port |
| <b>FEATURES &amp; SPECIFICATIONS</b>  |  |
| USB Hub Ports                         | Yes  |
| Number of USB Hub Ports               | 4  |
| USB Specification                     | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)                   |
| UASP Support                          | No   |
| Auto MDIX Support                     | No   |
| Full Duplex Support                   | No   |
| Suspend Mode Support                  | No   |
| Remote Wakeup Support                 | No   |
| Driver Required                       | No   |
| <b>STANDARDS &amp; COMPLIANCE</b>     |  |
| TAA Compliant Option                  | N  |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT                  |                                     |
| Product Warranty Period (Worldwide) | 3-year limited warranty             |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.