

SmartRack® Aisle Containment System


Configuration for 8 to 12 Standard-Width Racks, Wall-Facing (End)

Benefits

- Hot- and/or cold-aisle containment improves separation of hot and cold air to increase cooling efficiency and reduce costs
- Kits simplify ordering, include all required hardware and allow assembly, configuration and modification by non-specialists
- Modular and adjustable components work with standard or wide 42U, 45U and 48U rack cabinets, including aisle retrofits
- Locking doors control access, clear panels transmit room lighting and self-supporting design prevents excessive rack loading

Required Kits

- A** (2) **SRCTMTFRM** End Frame Kits
- B** (1) **SRCTMTTLBM** Telescopic Beam Kit (4 Beams)
- C** (1) **SRCTMTSDD** Sliding Double Door Kit
- D** (4 to 6) **SRCTMTCVR600** 600 mm Roof Panel Kits



Specifications

Configuration	SRACS003
Required Kits	(2) SRCTMTFRM , (1) SRCTMTTLBM , (1) SRCTMTSDD , (4 to 6) SRCTMTCVR600
Rack Height Compatibility	Any Combination of 42U, 45U and 48U*
Rack Width Compatibility	Standard (24 in. / 600 mm Nominal)
Rack Depth Compatibility	Any
Aisle Containment Type	Hot Aisle or Cold Aisle**
Warranty	5-Year Limited Warranty

* Add 3U and/or 6U riser panels (**SRCTMTR600SH** and/or **SRCTMTR600TL**) for installations with racks of varying heights. ** Hot-aisle containment requires user modification for exhaust air venting.

Visit tripplite.com/SRACS003 for More Information



Powering and Connecting Your World

1111 W. 35th Street, Chicago, IL 60609 USA | 773.869.1236 | tripplite.com